

09/20/99
jc712 U.S. PTO

IN THE U.S. PATENT AND TRADEMARK OFFICE

Docket No. 02005/0150

Transmitted herewith for filing is the patent application of

Inventor: Jeffrey B. Johnson

For: METHOD AND DEVICE FOR APPLYING ADHESIVES

Enclosed are:

- [X] Declaration and Power of Attorney
[X] Specification
[X] 5 (3 each) informal sheets of drawing
[X] An assignment of the invention to Capitol USA, LLC
[] A certified copy of a _____ application
[X] A verified statement to establish small entity status under 37 C.F.R. §1.9 and 37 C.F.R. §1.27.
[X] Information Disclosure Statement

The filing fee has been calculated as shown below:

FOR:	NO. FILED	NO. EXTRA
BASIC FEE		
TOTAL CLAIMS	26-20=	6
INDEP. CLAIMS	3-3=	0
[] MULTIPLE DEPENDENT CLAIM PRESENTED		
[] LATE-FILING SURCHARGE		

Small Entity	
RATE	FEE
	380
x 9=	54
x 39=	
+130	
TOTAL	434

Other than Small Entity	
RATE	FEE
	760
x 18=	0
x 78=	0
+260	
TOTAL	

- [] Please charge my Deposit Account No. _____ in the amount of \$ _____. A duplicate copy of this sheet is enclosed.
[X] The Commissioner is hereby authorized to charge any additional filing fees required under 37 C.F.R. §1.16, or credit any overpayment to Account No. 13-3403. A duplicate copy of this sheet is enclosed.
[X] A check in the amount of \$434.00 to cover the filing fee for the enclosed.
[X] A check in the amount of \$40.00 to cover the petition fee is enclosed.

Express Mail mailing label number EE267123038US

Date of Deposit:


I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

By: Stephen J. Stark

(Typed and printed name of person mailing paper or fee)

(Signature of person mailing paper or fee)

MILLER & MARTIN
1000 Volunteer Building
832 Georgia Avenue
Chattanooga, Tennessee 37402
(423) 766-6600

By: 
Douglas J. Johnson
Reg. No. 31,841

jc678 U.S. PTO
09/399385
09/20/99

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
)
JEFFREY B. JOHNSON)
)
 Serial No.)
)
 Filed: CONCURRENTLY)
)
 For: **METHOD AND DEVICE FOR APPLYING**)
ADHESIVES)

TRANSMITTAL

Commissioner of Patents and Trademarks
 Washington, D.C. 20231

Sir:

Transmitted herewith is a Declaration and Power of Attorney; Specification; Verified Statement Claiming Small Entity Status; Cover Sheet; an Assignment and an Assignment Cover Sheet; Information Disclosure Statement and Cover Sheet; checks in the amount of \$434.00 and \$40.00 to cover the filing fee and assignment recording fee; and three (3) sets of informal drawings for the above-referenced patent application. These documents are being transmitted pursuant to the provisions of 37 C.F.R. 1.10 via Express Mail.

Respectfully submitted,

MILLER & MARTIN

By: 

Douglas T. Johnson
 Reg. No. 31,841

1000 Volunteer Building
 832 Georgia Avenue
 Chattanooga, Tennessee 37402-2289
 (423) 756-6600

Our Docket No. 02005-0129

Express Mail mailing label number EE267123038US

Date of Deposit:

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Name of person mailing paper: Stephen J. Stark


 (Signature of person mailing paper)

SEP-20-99 MON 12:13 PM MILLER MARTIN LLP

FAX NO. 423 7858480

P. 02

Applicant or Patentee: Johnson

Attorney's

Serial or Patent No.:

Docket No.: 02005-0129Filed or Issued: ConcurrentlyTitle: METHOD AND DEVICE FOR APPLYING ADHESIVES

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(c))--SMALL BUSINESS CONCERN**

I hereby declare that I am

☐ the owner of the small business concern identified below:☒ an official of the small business concern empowered to act on behalf of the concern identified below:NAME OF SMALL BUSINESS CONCERN Capitol USA, L.L.C.ADDRESS OF SMALL BUSINESS CONCERN 300 Cross Plains Blvd., Dalton, Georgia 30720

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.12, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled METHOD AND DEVICE FOR APPLYING ADHESIVES by inventor(s) Jeff Johnson described in

☒ the specification filed herewith☐ application serial no. _____, filed _____☐ patent no. _____, issued _____

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights in the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e). *NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

NAME _____

ADDRESS _____

☐ INDIVIDUAL☐ SMALL BUSINESS CONCERN☐ NON PROFIT ORGANIZATION

NAME _____

ADDRESS _____

☐ INDIVIDUAL☐ SMALL BUSINESS CONCERN☐ NON PROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING Lisa VilandTITLE OF PERSON IF OTHER THAN OWNER VP AdministrationADDRESS OF PERSON SIGNING 300 Cross Plains Boulevard, Dalton, Georgia 30720SIGNATURE Lisa M. VilandDATE 09/20/99

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor: **Jeff Johnson**

TITLE: **METHOD AND DEVICE FOR APPLYING ADHESIVES**

Douglas T. Johnson
Reg. No. 31,841
Miller & Martin
Suite 1000, Volunteer Building
832 Georgia Avenue
Chattanooga, Tennessee 37402
(423) 756-6600
(423) 785-8480 - fax

METHOD AND DEVICE FOR APPLYING ADHESIVES

Field of the Invention

This invention relates to spraying devices, and in particular to a transportable adhesive sprayer system and method of applying adhesive, such as an adhesive utilized to adhere carpet to a floor.

Background of the Invention

In the art of applying adhesives for adhering carpet to a flooring or other material, a number of methods and/or systems have been developed. One method of applying carpet adhesive to a floor is to remove a supply of adhesive from a pail, such as a 5-gallon pail, and spread manually with a trowel or other device. This method of applying adhesive is labor intensive and may involve additional clean-up efforts compared to more automated methods. Furthermore, the adhesive is not in a closed container or system during the application process whereby foreign material could end up in the adhesive mixture by falling in the pail or by being inadvertently introduced by the manual spreaders.

Carpet adhesives normally come in pails, such as 5-gallon pails. One company, Roberts Consolidated Industries, Inc., of California, makes a spray adhesive system which is capable of dispensing adhesives directly from such a pail. The Roberts Spray Adhesive System utilizes a sprayer having an electric motor capable of delivering approximately ½ gallon of adhesive per minute. The pump utilized for that sprayer may be varied in speed to control the flow. The pump has a suction including a suction tube which may be deposited within an open bucket situated on the floor below the pump. The pump discharge goes through a length of hose and a spray gun extension in order to spray the adhesive on the flooring surface. This sprayer system

does not provide the capability of preventing contaminants from falling into the open bucket of adhesives. Additionally, the open bucket, when exposed to external atmospheric conditions over a period of time, will likely cause the adhesive to dry and/or cure in the bucket prior to being discharged through the sprayer gun. This may result in skinning in the bucket or clogging of parts of this spraying system. Additionally, significant clean up may be required after using this spraying system. Furthermore, the pail is not an integral part of the spray system so that each time a user desires to move the sprayer, the pail must be picked up and the sprayer moved and the user must be careful not to drip or spill the adhesive from the suction or from the pail. In short, the Roberts System is not a sealed system, is not as easily moved from room to room as desired, and may be messy to operate and clean.

A second type of adhesive spraying system known in the art is represented in a product built by the AAT Company. The AAT adhesive sprayer utilizes an air compressor which pressurizes a tank containing adhesives which are then forced through a nozzle in a sprayer. In general, pressurized systems are less favored for two principal reasons. First, in order to maintain a pressurized system, all of the seals and fittings need to be maintained so that they are capable of having an airtight seal. Secondly, in the event of a component failure, the potential for explosive adhesive release exists. One sprayer embodiment of the AAT variety utilizes an 8-gallon tank for the pressurized container. This pressurized tank becomes a pressure pot when filled with compressed air and adhesive. A small hole is located on top of the pressure pot for filling of the pressure pot with adhesives. This small hole is believed to make the filling of the pressure pot difficult, messy, and subject to spills. Once the adhesive is added to the tank, the tank is then closed and pressurized. During the filling of the container with the adhesive, the

adhesives come into contact with the atmosphere and the sprayer device is not a closed system. Debris or other foreign matter may enter into the pressure pot during the filling of the adhesives and some amount of skinning or clogging may occur. Additionally, skinning, curing and clogging may occur within the pressurized pressure pot. Furthermore, this device utilizes a sprayer similar to one which may be found in a self-service car wash station. There is no capability for this sprayer to have its tips switched according to the needs of the user.

The X-lent Equipment Company also markets sprayers which operates similar to the AAT product. One version plugs into an air compressor, while the other version has an air compressor as part of the system. These two products both utilize air in a pressure pot to force adhesive through a hose assembly and then through a sprayer having a nozzle. Essentially the compressor builds up pressure within the pressure pot and then the adhesive is blown out the bottom. This system is not a closed system because the pressure pot must be opened and exposed to the atmosphere for adhesive to be added, presenting curing and contamination issues. The pressurized air within the pressure pot is also believed to present curing and contamination issues. The system also suffers from the disadvantages of pressurized systems.

In the pressure pot systems where the adhesive is then disposed through a hose, the fluid dynamics of the pressure pot and hose are believed to result in a loss of head along the length of the hose. Accordingly, some versions of the X-lent products have maximum hose lengths of 75 feet, and some have a maximum length of 100 feet. With a 5 ½ horsepower motor attached to an 11 or 13 cubic feet per minute compressor with all X-lent pressure pot types, it is believed that there will be a maximum hose length for effective use.

Another manufacturer of pressurized spraying systems is TACC International Corporation located in Rockland, Maryland. The TACC Systems utilize a pressurized containers, similar to a propane tank, which has adhesive therein. These aerosol spray cans and cylinders are advertised as being highly portable, requiring no outside air or power support and available in both returnable and disposable cylinders. Although the TACC adhesives spraying systems are completely closed systems as far as the user is concerned, they are not refillable or reusable by the user without first returning the containers to the manufacturer for refilling.

As previously discussed, most carpet adhesives are sold in five gallon pails. One company, the Taylor Company, has previously sold carpet adhesives in a cardboard box. However, within their cardboard box was a baggie containing the adhesive. In order to utilize the adhesive within the baggie, the baggie was pulled up and around the cardboard box and the adhesive was scooped out. In use, the adhesive was exposed to atmospheric curing and contamination. It is not believed that this system was, or is, commercially successful.

Accordingly, a need exists for a closed adhesive spraying system, sprayer and method. Furthermore, a need exists to have an adhesive container system adapted for use in an atmospherically closed environment.

Summary of the Invention

Accordingly, it is an object of the invention to provide an adhesive spraying system and method with a positive displacement pump having a suction connected to a collapsible polyethylene container containing adhesives.

It is a further object of the invention to provide a portable spraying system.

It is another object of the invention to provide an adhesive spraying system which does not utilize a pressure pot.

It is a further object of the invention to provide an adhesive spraying system and method which prevents foreign matter and debris from contaminating the adhesive.

It is yet another object of the present invention to provide an adhesive spraying system to utilize at least two varieties of adhesives without extensive clean up to transition from one adhesive to another.

Still another object of the invention is the ability to utilize and store the adhesive sprayer system without clean up and then reutilize the sprayer system with minimal effort.

Accordingly, the method, system and sprayer disclosed herein include a positive displacement pump with the inlet connected to a dispensing nozzle of a reducible volume container. The reducible volume container may be located within a more rigid container such as a cardboard box. As the positive displacement pump is operated, a suction on the collapsible container is drawn by the positive displacement pump. The pump pumps the adhesive, or other material, preferably into an attached hose and through a bayonet type spray wand. The spray wand may have replaceable spray tips to alter the spray coverage, and may be activated by a trigger.

Brief Description of the Drawings

Fig. 1 is perspective view of the preferred embodiment of the spraying system and spraying device according to the present invention with a portion of the top of the sprayer shown in phantom.

Fig. 2 is a front plan view of the sprayer with the interior shown in phantom.

Fig. 3 is a back plan view of the device shown in Fig. 2.

Fig. 4A is perspective view of a cardboard box for housing a flexible container as utilized in the preferred embodiment.

Fig. 4 B is a perspective view of a partially filled flexible container utilized with the preferred embodiment.

Fig. 4 C is a perspective view of the cardboard box of Fig. 4A housing the flexible container of Fig. 4B.

Fig. 5 is a perspective view of the sprayer similar to Fig. 1 with an additional adhesive container attached.

Repeat use of reference numerals in the present specification represents like, similar and analogous parts, future drawings of the present invention throughout several views.

Detailed Description of the Preferred Embodiment

The present invention is concerned with the application of coatings including adhesives, and more specifically to a method, system and sprayer for applying adhesive, or another material, to a surface. Accordingly, Fig. 1 depicts the adhesive application system **10** including an adhesive container **20**, a sprayer **30**, and a spray wand **40**.

The adhesive container **20** is preferably a collapsible type container. One example of a presently preferred container is the type manufactured by Hedwin Company of Baltimore, Maryland. This container features a cardboard box **22** shown in Fig. 4A with an opening **24**. Fig. 4B is a reducible volume container **26** which fits within the cardboard box **22** as is illustrated in Fig. 4C. The reducible volume container **26** preferably has an opening, illustrated as a dispensing nozzle **28**, which may accept a screw on, or other type of cap and connectors. The

reducible volume container **26** may be constructed of linear low and low density polyethylene (“LDP”) manufactured in the form of a liner for use in the cardboard overpack **22**. The polyethylene container is designed to collapse as product is dispensed. The design is intended to allow product to flow from the polyethylene container in a continuous, uninterrupted stream. Alternatively, the reducible volume container **26** may be made of any other deformable material or materials. Additionally, the reducible volume container **26** could be constructed of more rigid materials such as a rigid tube with an end that moves within the tube to reduce the volume as the product is utilized, of the style typically employed with caulking compounds. Nevertheless, the cardboard box **22** with internal reducible volume container **26** has been found effective in storing and stacking the adhesive containers **20**. The cardboard box **22** may, or may not, be utilized depending on the particular application desired.

The preferred adhesive container **20** has about a five gallon capacity. Some pressure sensitive adhesives used with this system **10** have had an effective coverage area of approximately thirty or more square yards per gallon. Other adhesives such as vinyl adhesives and/or multipurpose adhesives may also be utilized with this spray system **10**. If multiple adhesive containers **20** are stacked on the sprayer **20** and connected to the pump, over 5000 square feet may be covered with adhesive without reloading.

The use of the reducible volume container **26** may allow the user to pump a container **26** dry without losing suction. If a plurality of reducible volume containers **26** are connected together, they may all be pumped from simultaneously. Alternatively, containers may be sequentially selected to be pumped from one at a time.

An adhesive container **20** is illustrated atop a portion of the sprayer **30** in Fig. 1.

Additionally containers **20** can be stacked alongside and on top of one another on the sprayer **30**.

If more than one container is utilized, such as containers **20, 90** illustrated in Fig. 5, more than one adhesive type may be dispensed from the plurality of containers **20, 80** without requiring cleaning of the system **10**. Although the container is illustrated in Fig. 1 as being at least partially held by recessed portion **32**, alternative and/or additional securing mechanisms including cinching belts, bungee cords and the like may be utilized. Alternatively, a user may not find it necessary to securely attach the container **20** to the sprayer **30**.

The adhesive container **20** is connected to the sprayer **30** by a supply tube **34**. A first end of the supply tube **34** with a connector **36** preferably attaches to the dispensing nozzle **28** of the reducible volume container **26**. The use of a T-joint on the first end of the supply tube **34** will permit it to be simultaneously attached to two adhesive containers **20**. The second opposed end of the supply tube **34** is preferably connected to the inlet of the pump **38** illustrated in Fig. 2. In order to access the pump and tubing, an access panel **42** may be located on the housing **44**. The pump **38** is preferably a positive displacement type pump such as a piston pump spray pump manufactured by Air Lestro Duratech. A suitable pump utilizes a 3/4 horsepower DC drive. A rheostat **46** may be utilized to control the pressure at the exit of the pump **38** as is illustrated in Fig. 3.

A first portion of the supply tube **34a** may be connected to a manifold **48**, shown in Fig. 2, especially if a plurality of containers **20, 90** are connected to the sprayer **30**. The manifold **48** will allow a user to select which of the first tube portions **34a** and containers **20, 90** are supplying adhesive through the second tube portion **34b** to the pump inlet **50**. A manifold **48** could allow

the use of quick disconnect connections from the supply tubes **34** to the manifold **48**. The manifold **48** may include valves and can be utilized to select the particular containers **20, 90**.

In a preferred embodiment, the pump **38** utilizes a standard 115 VAC electrical connection and draws approximately six amperes of current . The sprayer **30** may be parked near an electrical outlet and then use the spray hose **66** to conduct adhesive to the locations for application of the adhesives. Alternatively an electrical cable of sufficient length may be utilized to locate the sprayer **30** a significant distance from an electrical outlet. Additionally, the pump **38** may be supplied with electricity from a generator or other source.

The pump **38** is shown mounted within the housing **44** of the sprayer **30**. One or more brackets **52** may secure the pump **38** to the housing **44**. The housing **44** of the sprayer **30** is mounted on a mobile base as illustrated in Figs. 1-3 and 5. This hose utilizes four wheels, however other base designs may also be utilized. The two front wheels shown are swivel casters **56**. The two back wheels shown are tires, such as pneumatic tires **58**, mounted on axles **60**. A mobile base not only facilitates moving the sprayer about the buildings where adhesive is applied, but also in loading and unloading the sprayer on trucks for transportation between jobs.

A handle **62** connected to the mobile base and/or housing **44** is helpful in moving the sprayer **30**. A front platform **64** may serve as a bumper and may be utilized to store the spray wand **40** and hose **66** when moving the system **10**. The larger rear tires **58** have been found effective to allow users to roll the sprayer **30** on the back wheels like a dolly. Alternatively, the mobile base may be rolled on all four wheels. The housing **44** is preferably a sheet metal or plastic covering over a frame. Additionally, the housing **44** should be narrow enough to fit within most standard doorways.

The pump 38 is located within the housing 44 to minimize its exposure to dust and overspray. An on/off switch 84 may be utilized to turn the pump 38 on and off as shown in Fig. 3. Additionally, the pump 38 may have an optional drive control 88. This configuration for controls 80, 46, 84 has been found effective to minimize the cleanup required after using the system 10. In testing the embodiment illustrated and described herein, the sprayer 30 was operated with a container 20 of adhesives. The sprayer 30 and adhesive container 20 were left attached and stored. Approximately three weeks later, the same container 20 of adhesives was utilized after removing a small amount of adhesive that had settled in the spray tip 74 of the spray wand 40.

The pump outlet 68 is connected to outlet connector tube 70 as shown in Figure 2. The outlet connector tube 70 connects the pump outlet 68 to the spray hose 66 at outlet connection 72. The connection 72 allows for the removal of the hose 66 and spray wand 40.

The adhesive is preferably pulled by suction from adhesive containers 20 through supply tube 34 into the pump 38 and pumped out tube 70 to connection 72 and through the spray hose 66 to a spray nozzle. The spray hose 66 is preferably connected to a spray wand 40 at a connection, such as swivel connector 76. From the connection, the adhesive enters into the spray wand 40 past trigger switch 78. The trigger switch 78 may allow for controlling the flow of adhesive through the wand 40 or it may be an on/off type controller. From the trigger switch 78, adhesive flows through the wand tube 80 into the spray tip 74. The spray tip 74 may be permanently mounted to the wand tube 80 or may be removable and replaceable. In the removable configuration, a particular spray tip 74 may be selected for a particular application. Spray tips 74 having a 17mm to 27mm orifice have been found effective depending on the

particular coverage sought by the user of the spray system **10**. At least a portion of the spray wand **40**, such as bend **82**, may be angled in order to direct spray at a particular desired location. The particular spray wand **40** utilized is of the bayonet type, however a pistol grip, other type wands **40** may be utilized.

One preferred method of operation is to place a container **20** having adhesive material within the reducible volume container **26** therein atop the sprayer housing **44**. The supply tube **34** is connected to the container **20** and the pump inlet **50**. The pump outlet **68** is connected to a hose **66** attached to a spray wand **40**. The pump **38** within the sprayer **30** will be turned on and the trigger **78** on the spray wand **40** will direct when and where the adhesive is sprayed. Other methods of operation will incorporate other features of the system **10** taught herein and will be obvious to one skilled in the art.

What is claimed is:

1. A method of applying an adhesive to a surface comprising the steps of :
 - a) connecting a reducible volume container having a first volume to an inlet of a pump, said reducible volume container having a supply of an adhesive therein;
 - b) connecting the outlet of the pump to a spray device;
 - c) actuating the pump; and
 - d) spraying at least a portion of the adhesive out of the spray wand, whereby after spraying said at least a portion of the adhesive from the spray device said reducible volume container having a second volume, said second volume being less than said first volume.
2. The method of claim 1 wherein the spray device further comprises a spray wand.
3. The method of claim 2 further comprising the step of activating a trigger on the spray wand to control the spray.
4. The method of claim 1 wherein the pump is a positive displacement pump.
5. The method of claim 1 wherein the reducible volume container is constructed at least in part of a low density polypropylene.
6. The method of claim 6 wherein the reducible volume container is substantially enclosed within a box.
7. The method claim 1 wherein the reducible volume container, the pump and the spray device comprise a substantially closed system.

8. The method of claim 1 wherein the reducible volume container, the pump and the spray wand prevent the adhesive from substantial exposure to atmospheric conditions until the adhesive is sprayed from the spray device.
9. The method of claim 1 wherein a second reducible volume container, is selectively connected to the inlet of the pump.
10. The method of claim 1 wherein the pressure within the reducible volume container is less than or equal to the pressure exterior to the reducible volume container.
11. An adhesive application system comprising:
a first reducible volume container having a supply of adhesive therein, in closed and selectable communication with a spray device, whereby said first reducible volume container selectably communicates with an inlet at a pump and the spray device communicates with an outlet of the pump.
12. The adhesive application system of claim 11 wherein the pressure within the reducible volume container is less than or equal to the pressure exterior to the first reducible volume container.
13. The coating application system of claim 11 wherein the first reducible volume container is comprised of a collapsible plastic material.
14. The coating application system of claim 13 wherein the first reducible volume container is substantially enclosed within a box.
15. The coating application system of claim 11 wherein the pump is mounted on a mobile base.

16. The coating application system of claim 11 further comprising a manifold intermediate the first reducible volume container and the pump inlet.
17. The coating application system of claim 16 further comprising a second reducible volume container having a supply of coating therein, said second reducible volume container in communication with the manifold through a dispensing nozzle.
18. The coating application system of claim 16 wherein the adhesives in the first and second reducible volume containers are chemically distinct.
19. The coating application of claim 11 wherein the first reducible volume container is in selective communication with the inlet of the pump.
20. The coating application system of claim 11 further comprising a second reducible volume container having a supply of coating therein, said second reducible volume container in selective communication with the inlet of the pump through a dispensing nozzle.
21. The coating application system of claim 20 wherein at least one valve is utilized to achieve the selective communication between the second reducible volume container and the inlet of the pump.
22. A container for adhesives comprising:
a reducible volume container having a supply of adhesive coating therein, said reducible volume container connectable to a pump through a dispensing nozzle,

said dispensing nozzle adapted to seal in closed communication with a tube
connected to a pump; and
an outer box substantially enclosing said reducible volume container.

23. The container for adhesives of claim 22 wherein the reducible volume container is constructed at least in part of a low density polypropylene.
24. The container for adhesives of claim 22 wherein the dispensing nozzle is threaded.
25. The container for adhesives of claim 24 wherein the dispensing nozzle has male threads.
26. The container for adhesives of claim 25 wherein the dispensing nozzle has female threads.

Abstract of the Disclosure

A method, system and sprayer for applying adhesives, or other coatings, is disclosed herein including a positive displacement pump having an inlet connected through a dispensing nozzle to a reducible volume container. The reducible volume container may be located in a more rigid container such as a cardboard box. As the positive displacement pump is operated, a suction on the collapsible container is drawn by the positive displacement pump. The pump may pump adhesives, or any other fluid material, preferably into an attached hose and through a bayonet type spray wand. The spray wand may have a replaceable tip to alter the spray coverage and may be activated by a trigger.

17

3/4 view





FIG 1

FIG 1 is a perspective view of the device in accordance with the present invention.

FIG 2






FIG 3






FIG 4A

FIG 4C

FIG 4B

3/4 v. en




Fig 5

[illegible]

RULE 63 (37 C.F.R. 1.63)
DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND DEVICE FOR APPLYING ADHESIVES

the specification of which (check applicable box(s):

[X] is attached hereto.

[] was filed on _____ as U.S. Application Serial No. _____.

[] was filed as PCT International application No. PCT// on _____
and (if applicable to U.S. or PCT application) was amended on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 C.F.R. 1.56(a). I hereby claim foreign priority benefits under 35 U.S.C. 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed or, if no priority is claimed, before the filing date of this application:


Prior Foreign Application(s): Application Number	Country	Day/Month/Year Filed
---	---------	----------------------

I hereby claim the benefit under 35 U.S.C. 120/365 of all prior United States and PCT international applications listed above or below and, insofar as the subject matter of each of the claims of this application is not disclosed in such prior applications in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose material information as defined in 37 C.F.R. 1.56(a) which occurred between the filing of the prior application and the national or PCT international filing date of this application:

Prior U.S./PCT Application(s): Application Serial No.	Day/Month/Year Filed	Status; patented, pending, abandoned
--	----------------------	---

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

And I hereby appoint Alan Ruderman, Reg. No. 25,369, Douglas T. Johnson, Reg. No. 31,841, Charles W. Forlidas, Reg. No. 41,758, and Stephen J. Stark, Reg. No. 43,152, with the law firm of Miller & Martin, 1000 Volunteer Building, 832 Georgia Avenue, Chattanooga, Tennessee 37402, telephone number (423) 756-6600, my attorney to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent and to whom all communications are to be directed.

1) Inventor's Signature  Date 9/16/95
Inventor's Name (typed) Jeff Johnson USA
First Middle Initial Family Name Citizenship
Residence (City) Dalton (State/Foreign Country) GA
Post Office Address 300 Cross Plains Blvd. Zip Code 30720

2) Inventor's Signature _____ Date _____
Inventor's Name (typed) _____
First Middle Initial Family Name Citizenship
Residence (City) _____ (State/Foreign Country) _____
Post Office Address _____ Zip Code _____

3) Inventor's Signature _____ Date _____
Inventor's Name (typed) _____
First Middle Initial Family Name Citizenship
Residence (City) _____ (State/Foreign Country) _____
Post Office Address _____ Zip Code _____

FOR ADDITIONAL INVENTORS, check box ☐ and attach sheet with same information and signature and date for each.